

The Compressor Range

MODEL	CFM	CFM FAD @ 100 PSI	HP	VOLTS / PHASE	AIR RECEIVER LTR'S
HV6	5.50	3.74	1.00	230 / 415	37
HV8	7.80	4.90	1.50	230 / 415	50
HV12	11.00	7.40	2.00	230	100
HV12	11.00	7.40	2.00	415	100
HW16	16.00	10.60	3.00	230	100
HW16	16.00	10.60	3.00	415	100
HW16	16.00	10.60	3.00	230	150
HW16	16.00	10.60	3.00	415	150
HW16	16.00	10.60	3.00	230	200
HW16	16.00	10.60	3.00	415	200
HW16 TANDEM	32.00	21.20	3 + 3	230	272
H21	21.00	14.70	4.00	230	200
H21	21.00	14.70	4.00	415	200
H21 / 200PSI	21.00	14.70	4.00	415	200
H23	22.80	16.70	5.50	415	200
HW25	23.00	17.20	5.50	415	200
HW25 / 200PSI	23.00	17.20	5.50	415	200
HW25 INVERTER	23.00	17.20	5.50	230	200
H32	31.00	24.80	7.50	415	270
H32 / 200PSI	31.00	24.50	7.50	415	270
HW32	33.00	24.70	7.50	415	270
HW45 / DUAL CON	41.00	31.00	10.00	415	270
HW45 / 200PSI	41.00	31.00	10.00	415	270
HW50 / DUAL CON	48.00	33.00	10.00	415	270
HW65 / DUAL CON	60.00	46.40	15.00	415	270
HW56 / 200 PSI	60.00	46.40	15.00	415	270
HW85 / DUAL CON	82.50	54.00	15.00	415	270